

Package ‘LMoFit’

May 14, 2024

Type Package

Title Advanced L-Moment Fitting of Distributions

Version 0.1.7

Description A complete framework for frequency analysis is provided by 'LMoFit'. It has functions related to the determination of sample L-moments as in Hosking, J.R.M. (1990) <[doi:10.1111/j.2517-6161.1990.tb01775.x](https://doi.org/10.1111/j.2517-6161.1990.tb01775.x)>, the fitting of various distributions as in Zaghoul et al. (2020) <[doi:10.1016/j.advwatres.2020.103720](https://doi.org/10.1016/j.advwatres.2020.103720)> and Hosking, J.R.M. (2019) <<https://CRAN.R-project.org/package=lmom>>, besides plotting and manipulating L-space diagrams as in Papalexiou, S.M. & Koutsoyianis, D. (2016) <[doi:10.1016/j.advwatres.2016.05.005](https://doi.org/10.1016/j.advwatres.2016.05.005)> for two-shape parametric distributions on the L-moment ratio diagram. Additionally, the quantile, probability density, and cumulative probability functions of various distributions are provided in a user-friendly manner.

Maintainer Mohanad Zaghoul <mohanad.zaghoul@usask.ca>

Depends R (>= 3.3)

Imports lmom, pracma, stats, ggplot2, sf, utils

License GPL-3

Encoding UTF-8

LazyData true

LazyDataCompression xz

RoxygenNote 7.1.0

VignetteBuilder knitr

Suggests knitr, rmarkdown

NeedsCompilation no

Author Mohanad Zaghoul [aut, cre],
Simon Michael Papalexiou [aut, ths],
Amin Elshorbagy [aut, ths]

Repository CRAN

Date/Publication 2024-05-14 07:33:23 UTC

R topics documented:

com_sam_lspace	3
con_samlmom_lspace	4
con_sam_lspace	5
dBrIII	6
dBrXII	7
dgam	7
dgev	8
dGG	9
dglo	9
dgno	10
dgpa	11
dln3	11
dnor	12
dpe3	13
fit_BrIII	13
fit_BrXII	14
fit_gam	15
fit_gev	15
fit_GG	16
fit_glo	17
fit_gno	18
fit_gpa	18
fit_ln3	19
fit_nor	20
fit_pe3	21
FLOW_AMAX	21
FLOW_AMAX_MULT	22
get_julian	23
get_sample_lmom	23
lspace_BrIII	24
lspace_BrIII.xy	25
lspace_BrXII	25
lspace_BrXII.xy	26
lspace_GG	27
lspace_GG.xy	27
pBrIII	28
pBrXII	29
pemp	29
pgam	30
pgev	31
pGG	31
pglo	32
pgno	33
pgpa	33
pln3	34
pnor	35

ppe3	35
qBrIII	36
qBrXII	37
qgam	37
qgev	38
qGG	39
qglo	40
qgno	40
qgpa	41
qln3	42
qnor	43
qpe3	43
tBrIII	44
tBrXII	45
tgam	45
tgev	46
tGG	47
tglo	47
tgno	48
tgpa	49
tln3	49
tnor	50
tpe3	51

Index	52
--------------	-----------

com_sam_lspace	<i>Comparing sample L-moment ratios with L-spaces of various distributions on the L-moments ratio diagram</i>
----------------	---

Description

Comparing sample L-moment ratios with L-spaces of various distributions on the L-moments ratio diagram

Usage

```
com_sam_lspace(sample, type = "m", Dist = "BrIII", color = "red", shape = 8)
```

Arguments

sample	for a single site, sample is a vector of observations, e.x. FLOW_AMAX. For multiple sites, sample is a dataframe consisting of multiple columns where each column has the data observed at one site; this dataframe should have column names as station names, e.x. FLOW_AMAX_MULT.
type	the type of the sample. It can be "s" for single site, the default, or "m" for multiple sites.

Dist	select the distribution to plot its L-space in the background. This can be "BrIII" for Burr Typr-III distribution, "BrXII" for Burr Typr-XII distribution, or "GG" for Generalized Gamma distribution. The default Dist is "BrIII".
color	color of the L-point/s, default is "red".
shape	shape of the L-point/s, default is 8.

Value

ggplot plot comparing sample/s L-point/s with L-space of a distribution on the L-moment ratio diagram

Author(s)

Mohanad Zaghloul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
com_plot_BrIII <- com_sam_lspace(LMoFit::FLOW_AMAX, type = "s", Dist = "BrIII")
com_plot_BrXII <- com_sam_lspace(LMoFit::FLOW_AMAX, type = "s", Dist = "BrXII")
com_plot_GG <- com_sam_lspace(LMoFit::FLOW_AMAX, type = "s", Dist = "GG")
com_plot_BrIII <- com_sam_lspace(LMoFit::FLOW_AMAX_MULT, type = "m", Dist = "BrIII")
com_plot_BrXII <- com_sam_lspace(LMoFit::FLOW_AMAX_MULT, type = "m", Dist = "BrXII")
com_plot_GG <- com_sam_lspace(LMoFit::FLOW_AMAX_MULT, type = "m", Dist = "GG")
```

con_samlmom_lspace *Condition of sample lpoints, as inside/outside of specific L-spaces on the L-moments ratio diagram, using sample lmoments.*

Description

Condition of sample lpoints, as inside/outside of specific L-spaces on the L-moments ratio diagram, using sample lmoments.

Usage

```
con_samlmom_lspace(samplelmom, Dist = "BrIII")
```

Arguments

samplelmom	L-moments as c(l1, l2, l3, l4, t2, t3, t4). Use get_sample_lmom() to obtain these lmoments.
Dist	select the distribution to plot its L-space in the background. This can be "BrIII" for Burr Typr-III distribution, "BrXII" for Burr Typr-XII distribution, or "GG" for Generalized Gamma distribution. The default Dist is "BrIII". The default is set to BrIII.

Value

The condition of the L-points in regards to the selected L-space as inside or outside.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
sample <- LMoFit::FLOW_AMAX
samplelmom <- get_sample_lmom(x = sample)
con_samlmom_lspace(samplelmom, Dist = "BrIII")
con_samlmom_lspace(samplelmom, Dist = "BrXII")
con_samlmom_lspace(samplelmom, Dist = "GG")
```

con_sam_lspace	<i>Condition of sample lpoints, as inside/outside of specific L-spaces on the L-moments ratio diagram, using sample.</i>
----------------	--

Description

Condition of sample lpoints, as inside/outside of specific L-spaces on the L-moments ratio diagram, using sample.

Usage

```
con_sam_lspace(sample, type = "s", Dist = "BrIII")
```

Arguments

sample	for a single site, sample is a vector of observations, e.x. FLOW_AMAX. For multiple sites, sample is a dataframe consisting of multiple columns where each column has the data observed at one site; this dataframe should have column names as station names, e.x. FLOW_AMAX_MULT.
type	the type of the sample. It can be "s" for single site, the default, or "m" for multiple sites.
Dist	select the distribution to plot its L-space in the background. This can be "BrIII" for Burr Typr-III distribution, "BrXII" for Burr Typr-XII distribution, or "GG" for Generalized Gamma distribution. The default Dist is "BrIII".

Value

The condition of the L-points in regards to the selected L-space as inside or outside.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
con_sam_lspace(LMoFit::FLOW_AMAX, type = "s", Dist = "BrIII")
con_sam_lspace(LMoFit::FLOW_AMAX, type = "s", Dist = "BrXII")
con_sam_lspace(LMoFit::FLOW_AMAX, type = "s", Dist = "GG")
con_sam_lspace(LMoFit::FLOW_AMAX_MULT, type = "m", Dist = "BrIII")
con_sam_lspace(LMoFit::FLOW_AMAX_MULT, type = "m", Dist = "BrXII")
con_sam_lspace(LMoFit::FLOW_AMAX_MULT, type = "m", Dist = "GG")
```

dBrIII

Probability density function of BrIII distribution

Description

Probability density function of BrIII distribution

Usage

```
dBrIII(x, para = c(1, 2, 0.5))
```

Arguments

x	quantile/s
para	parameters as c(scale, shape1, shape2)

Value

Probability density function

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
d <- dBrIII(x = 108.4992, para = c(10, 0.25, 0.5))
```

dBrXII *Probability density function of BrXII distribution*

Description

Probability density function of BrXII distribution

Usage

```
dBrXII(x, para = c(1, 2, 0.5))
```

Arguments

x	quantile/s
para	parameters as c(scale, shape1, shape2)

Value

Probability density function

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
d <- dBrXII(x = 108.4992, para = c(10, 0.25, 0.5))
```

dgam *Probability density function of Gamma distribution*

Description

Probability density function of Gamma distribution

Usage

```
dgam(x, para = c(1, 2, 0.5))
```

Arguments

x	quantile/s
para	parameters as c(shape, scale)

Value

Probability density function

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
d <- dgam(x = 0.1, para = c(0.1, 0.2))
```

dgev

Probability density function of GEV distribution

Description

Probability density function of GEV distribution

Usage

```
dgev(x, para)
```

Arguments

x	quantile/s
para	parameters as c(location, scale, shape)

Value

Probability density function

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
d <- dgev(x = 108.4992, para = c(10, 1, 1))
```

dGG *Probability density function of Generalized Gamma (GG) distribution*

Description

Probability density function of Generalized Gamma (GG) distribution

Usage

```
dGG(x, para = c(10, 0.25, 0.5))
```

Arguments

x	quantile/s
para	parameters as c(scale, shape1, shape2)

Value

Probability density function

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
d <- dGG(x = 108.4992, para = c(10, 0.25, 0.5))
```

dglo *Probability density function of Generalized Logistic Distribution*

Description

Probability density function of Generalized Logistic Distribution

Usage

```
dglo(x, para = c(1, 2, 0.5))
```

Arguments

x	quantile/s
para	parameters as c(location, scale, shape)

Value

Probability density function

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
d <- dglo(x = 0.1, para = c(1, 2, 0.5))
```

dgno

Probability density function of Generalized normal Distribution

Description

Probability density function of Generalized normal Distribution

Usage

```
dgno(x, para = c(1, 2, 0.5))
```

Arguments

x	quantile/s
para	parameters as c(location, scale, shape)

Value

Probability density function

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
d <- dgno(x = 0.1, para = c(1, 2, 0.5))
```

dgpa *Probability density function of Generalized Pareto Distribution*

Description

Probability density function of Generalized Pareto Distribution

Usage

```
dgpa(x, para)
```

Arguments

x	quantile/s
para	parameters as c(location, scale, shape)

Value

Probability density function

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
d <- dgpa(x = 0.1, para = c(1, 2, 0.5))
```

dln3 *Probability density function of Lognormal-3 Distribution*

Description

Probability density function of Lognormal-3 Distribution

Usage

```
dln3(x, para = c(0, 0, 1))
```

Arguments

x	quantile/s
para	parameters as c(zeta, mu, sigma) that is c(lower bound, mean on log scale, standard deviation on log scale).

Value

Probability density function

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
d <- dln3(x = 12, para = c(0, 0, 1))
```

dnor

Probability density function of Normal Distribution

Description

Probability density function of Normal Distribution

Usage

```
dnor(x, para = c(1, 2))
```

Arguments

x	quantile/s
para	parameters as c(location, scale)

Value

Probability density function

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
d <- dnor(x = 1.5, para = c(1, 2))
```

dpe3 *Probability density function of Pearson type-3 Distribution*

Description

Probability density function of Pearson type-3 Distribution

Usage

```
dpe3(x, para = c(10, 1, 1.5))
```

Arguments

x	quantile/s
para	parameters as c(mu, sigma, gamma) that is c(location, scale, shape).

Value

Probability density function

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
d <- dpe3(x = 12, para = c(10, 1, 1.5))
```

fit_BrIII *Fit Burr Type-III (BrIII) Distribution*

Description

Fit Burr Type-III (BrIII) Distribution

Usage

```
fit_BrIII(s1, st2, st3)
```

Arguments

s1	1st l-moments
st2	2nd l-moment ratio
st3	3rd l-moment ratio

Value

A dataframe containing the scale parameter, the shape1 parameter, the shape2 parameter, the squared error of scale parameter, and the squared error of shape parameter

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
BrIII_par_valid <- fit_BrIII(s11 = 10, st2 = 0.25, st3 = 0.1)
BrIII_par_invalid <- fit_BrIII(s11 = 10, st2 = 0.5, st3 = 0.8)
```

fit_BrXII

Fit Burr Type-XII (BrXII) Distribution

Description

Fit Burr Type-XII (BrXII) Distribution

Usage

```
fit_BrXII(s11, st2, st3)
```

Arguments

s11	1st l-moments
st2	2nd l-moment ratio
st3	3rd l-moment ratio

Value

A dataframe containing the scale parameter, the shape1 parameter, the shape2 parameter, the squared error of the scale parameter, and the squared error of the shape parameters.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
BrXII_par_valid <- fit_BrXII(s11 = 10, st2 = 0.25, st3 = 0.25)
BrXII_par_invalid <- fit_BrXII(s11 = 10, st2 = 0.5, st3 = 0.8)
```

`fit_gam`*Fit Gamma distribution using the 'lmom' package*

Description

Fit Gamma distribution using the 'lmom' package

Usage

```
fit_gam(s11, s12, st3, st4)
```

Arguments

s11	sample 1st l-moment
s12	sample 2nd l-moment
st3	sample 3rd l-moment ratio
st4	sample 4th l-moment ratio

Value

A vector of parameters as alpha (shape) and beta (scale).

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
gam_par <- fit_gam(15, 1.7, 0.04, -0.02)
```

`fit_gev`*Fit GEV distribution*

Description

Fit GEV distribution

Usage

```
fit_gev(s11, s12, st3)
```

Arguments

s11	sample 1st l-moment
s12	sample 2nd l-moment
st3	sample 3rd l-moment ratio

Value

A dataframe containing the location parameter, the scale parameter, the shape parameter, and the squared error of shape parameters.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
GEV_par <- fit_gev(s11 = 10, s12 = 0.5, st3 = 0.8)
```

fit_GG

Fit Generalized Gamma (GG) Distribution

Description

Fit Generalized Gamma (GG) Distribution

Usage

```
fit_GG(s11, st2, st3)
```

Arguments

s11	1st l-moments
st2	2nd l-moment ratio
st3	3rd l-moment ratio

Value

A dataframe containing the scale parameter, the shape1 parameter, the shape2 parameter, the squared error of scale parameter, and the squared error of shape parameters.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
GG_par_valid <- fit_GG(s11 = 10, st2 = 0.4, st3 = 0.2)
GG_par_invalid <- fit_GG(s11 = 1, st2 = 0.25, st3 = 0.25)
```

`fit_glo`*Fit Generalized Logistic distribution using the 'lmom' package*

Description

Fit Generalized Logistic distribution using the 'lmom' package

Usage

```
fit_glo(s11, s12, st3, st4)
```

Arguments

s11	sample 1st l-moment
s12	sample 2nd l-moment
st3	sample 3rd l-moment ratio
st4	sample 4th l-moment ratio

Value

A vector of parameters as xi (location), alpha (scale), and k (shape).

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
glo_par <- fit_glo(15, 1.7, 0.04, -0.02)
```

`fit_gno`*Fit Generalized Normal distribution using the 'lmom' package*

Description

Fit Generalized Normal distribution using the 'lmom' package

Usage

```
fit_gno(s11, s12, st3, st4)
```

Arguments

<code>s11</code>	sample 1st l-moment
<code>s12</code>	sample 2nd l-moment
<code>st3</code>	sample 3rd l-moment ratio
<code>st4</code>	sample 4th l-moment ratio

Value

A vector of parameters as xi (location), alpha (scale), and k (shape).

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
gno_par <- fit_gno(15, 1.7, 0.04, -0.02)
```

`fit_gpa`*Fit Generalized Pareto distribution using the 'lmom' package*

Description

Fit Generalized Pareto distribution using the 'lmom' package

Usage

```
fit_gpa(s11, s12, st3, st4)
```

Arguments

s11	sample 1st l-moment
s12	sample 2nd l-moment
st3	sample 3rd l-moment ratio
st4	sample 4th l-moment ratio

Value

A vector of parameters as xi (location), alpha (scale), and k (shape).

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
gpa_par <- fit_gpa(15, 1.7, 0.04, -0.02)
```

fit_ln3

Fit LogNormal-3 distribution using the 'lmom' package

Description

Fit LogNormal-3 distribution using the 'lmom' package

Usage

```
fit_ln3(s11, s12, st3, st4)
```

Arguments

s11	sample 1st l-moment
s12	sample 2nd l-moment
st3	sample 3rd l-moment ratio
st4	sample 4th l-moment ratio

Value

A vector of parameters as zeta (lower bound), mu (mean on log-scale), and sigma (st.dev. on log-scale)

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
ln3_par <- fit_ln3(15, 1.7, 0.04, -0.02)
```

fit_nor

Fit Normal distribution using the 'lmom' package

Description

Fit Normal distribution using the 'lmom' package

Usage

```
fit_nor(s11, s12, st3, st4)
```

Arguments

s11	sample 1st l-moment
s12	sample 2nd l-moment
st3	sample 3rd l-moment ratio
st4	sample 4th l-moment ratio

Value

A vector of parameters as mu (location) and sigma (scale).

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
nor_par <- fit_nor(15, 1.7, 0.04, -0.02)
```

fit_pe3	<i>Fit Pearson Type-3 distribution using the 'lmom' package</i>
---------	---

Description

Fit Pearson Type-3 distribution using the 'lmom' package

Usage

```
fit_pe3(s11, s12, st3, st4)
```

Arguments

s11	sample 1st l-moment
s12	sample 2nd l-moment
st3	sample 3rd l-moment ratio
st4	sample 4th l-moment ratio

Value

A vector of parameters as mu (location), sigma (scale), and gamma (shape).

Author(s)

Mohanad Zaghloul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
pe3_par <- fit_pe3(15, 1.7, 0.04, -0.02)
```

FLOW_AMAX	<i>Annual maximum flow data at Water Survey of Canada WSC flow gauge number 08NA002 in BC, Vancouver, Canada. Lat: 51°14'36.8" N, Long: 116°54'46.6" W.</i>
-----------	---

Description

Annual maximum flow data at Water Survey of Canada WSC flow gauge number 08NA002 in BC, Vancouver, Canada. Lat: 51°14'36.8" N, Long: 116°54'46.6" W.

Usage

```
FLOW_AMAX
```

Format

A vector of observations of length equal to 112

flow annual maximum flow observed per each year at one site

Source

coded in data-raw

FLOW_AMAX_MULT	<i>Annual maximum flow data at 10 hypothetical flow gauge.</i>
----------------	--

Description

Annual maximum flow data at 10 hypothetical flow gauge.

Usage

FLOW_AMAX_MULT

Format

A data frame with 112 rows and 10 variables:

flow_st1 annual maximum flow observed per each year at site 1

flow_st2 annual maximum flow observed per each year at site 2

flow_st3 annual maximum flow observed per each year at site 3

flow_st4 annual maximum flow observed per each year at site 4

flow_st5 annual maximum flow observed per each year at site 5

flow_st6 annual maximum flow observed per each year at site 6

flow_st7 annual maximum flow observed per each year at site 7

flow_st8 annual maximum flow observed per each year at site 8

flow_st9 annual maximum flow observed per each year at site 9

flow_st10 annual maximum flow observed per each year at site 10

Source

coded in data-raw

get_julian	<i>Get julian date from the begining of the year</i>
------------	--

Description

Get julian date from the begining of the year

Usage

```
get_julian(x)
```

Arguments

x date or a series of dates such as, as.Date("yyyy-mm-dd")

Value

A julian date between 1 and 365, note that in leap years the day 366 is considered as 365

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
get_julian(x = as.Date("1979-01-15"))
```

get_sample_lmom	<i>Estimate sample L-moments and L-moment ratios</i>
-----------------	--

Description

Estimate sample L-moments and L-moment ratios

Usage

```
get_sample_lmom(x)
```

Arguments

x a series of quantiles

Value

A dataframe containing the 1st l-moment, the 2nd l-moment, the 3rd l-moment, the 4th l-moment, the 2nd l-moment ratio "L-variation", the 3rd l-moment ratio "L-skewness", and the 4th l-moment ratio "L-kurtosis"

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
sample_lmom <- get_sample_lmom((rnorm(n = 500, mean = 10, sd = 0.5)))
```

lspace_BrIII

L-space of Burr Type-III Distribution (BrIII)

Description

This is a plot of the L-space of BrIII Distribution with L-variation on x-axis and L-skewness on y-axis. The L-space is bounded by shape1 in the range of 0.01 to 150.01, and by shape2 in the range of 0.005 to 0.999.

Usage

```
lspace_BrIII
```

Format

A ggplot

data

layers

scales

mapping

theme

coordinates

facet

plot_env

labels

Source

coded in data-raw

lspace_BrIII.xy	<i>coordinates of the L-space of Burr Type-III Distribution (BrIII)</i>
-----------------	---

Description

This is a plot of the L-space of BrIII Distribution with L-variation on x-axis and L-skewness on y-axis. The L-space is bounded by shape1 in the range of 0.01 to 150.01, and by shape2 in the range of 0.005 to 0.999.

Usage

```
lspace_BrIII.xy
```

Format

A ggplot

x l-variation "t2"

y l-skewness "t3"

Source

coded in data-raw

lspace_BrXII	<i>L-space of Burr Type-XII Distribution (BrXII)</i>
--------------	--

Description

This is a plot of the L-space of BrXII Distribution with L-variation on x-axis and L-skewness on y-axis. The L-space is bounded by shape1 in the range of 0.1 to 150, and by shape2 in the range of 0.001 to 1.

Usage

```
lspace_BrXII
```

Format

A ggplot

data

layers

scales

mapping

theme
coordinates
facet
plot_env
labels

Source

coded in data-raw

lspace_BrXII.xy *coordinates of the L-space of Burr Type-XII Distribution (BrXII)*

Description

This is a plot of the L-space of BrXII Distribution with L-variation on x-axis and L-skewness on y-axis. The L-space is bounded by shape1 in the range of 0.1 to 150, and by shape2 in the range of 0.001 to 1.

Usage

lspace_BrXII.xy

Format

A ggplot

x l-variatoin "t2"

y l-skewness "t3"

Source

coded in data-raw

`lspace_GG`*L-space of Generalized Gamma Distribution (GG)*

Description

This is a plot of the L-space of GG Distribution with L-variation on x-axis and L-skewness on y-axis. The L-space is bounded by shape1 in the range of 0.1 to 5.9, and by shape2 in the range of 0.19 to 38.

Usage`lspace_GG`**Format**

A ggplot

data**layers****scales****mapping****theme****coordinates****facet****plot_env****labels****Source**

coded in data-raw

`lspace_GG.xy`*coordinates of the L-space of Generalized Gamma Distribution (GG)*

Description

This is a plot of the L-space of GG Distribution with L-variation on x-axis and L-skewness on y-axis. The L-space is bounded by shape1 in the range of 0.1 to 5.9, and by shape2 in the range of 0.19 to 38.

Usage`lspace_GG.xy`

Format

A ggplot

x l-variatoin "t2"

y l-skewness "t3"

Source

coded in data-raw

pBrIII

Cumulative distribution function of BrIII distribution

Description

Cumulative distribution function of BrIII distribution

Usage

```
pBrIII(x, para = c(1, 2, 0.5))
```

Arguments

x quantile/s

para parameters as c(scale, shape1, shape2)

Value

Non-exceedance probability from the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
u <- pBrIII(x = 108.4992, para = c(10, 0.25, 0.5))
```

pBrXII *Cumulative distribution function of BrXII distribution*

Description

Cumulative distribution function of BrXII distribution

Usage

```
pBrXII(x, para = c(1, 2, 0.5))
```

Arguments

x	quantile/s
para	parameters as c(scale, shape1, shape2)

Value

Non-exceedance probability from the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
u <- pBrXII(x = 108.4992, para = c(10, 0.25, 0.5))
```

pemp *Emperical cumulative distribution function*

Description

Emperical cumulative distribution function

Usage

```
pemp(data)
```

Arguments

data	quantile/s
------	------------

Value

A dataframe containing two columns as the sorted observations and the corresponding empirical probability of non-exceedance

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
output <- pemp(data = runif(n = 50, min = 10, max = 100))
```

pgam

Cumulative distribution function of Gamma distribution

Description

Cumulative distribution function of Gamma distribution

Usage

```
pgam(x, para = c(1.5, 1))
```

Arguments

x	quantile/s
para	parameters as c(shape, scale)

Value

Non-exceedance probability from the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
u <- pgam(x = 0.1, para = c(0.1, 0.2))
```

pgev

Cumulative distribution function of GEV distribution

Description

Cumulative distribution function of GEV distribution

Usage

```
pgev(x, para)
```

Arguments

x	quantile/s
para	parameters as c(location, scale, shape)

Value

Non-exceedance probability from the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
u <- pgev(x = 108.4992, para = c(10, 1, 1))
```

pGG

Cumulative distribution function of Generalized Gamma (GG) distribution

Description

Cumulative distribution function of Generalized Gamma (GG) distribution

Usage

```
pGG(x, para = c(10, 0.25, 0.5))
```

Arguments

x	quantile/s
para	parameters as c(scale, shape1, shape2)

Value

Non-exceedance probability from the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
u <- pGG(x = 108.4992, para = c(10, 0.25, 0.5))
```

pglo

Cumulative distribution function of Generalized Logistic Distribution

Description

Cumulative distribution function of Generalized Logistic Distribution

Usage

```
pglo(x, para = c(10, 1.5, 1))
```

Arguments

x	quantile/s
para	parameters as c(location, scale, shape)

Value

Non-exceedance probability from the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
u <- pglo(x = 0.1, para = c(10, 0.1, 0.2))
```

pgno *Cumulative distribution function of Generalized Normal Distribution*

Description

Cumulative distribution function of Generalized Normal Distribution

Usage

```
pgno(x, para = c(10, 1.5, 1))
```

Arguments

x	quantile/s
para	parameters as c(location, scale, shape)

Value

Non-exceedance probability from the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
u <- pgno(x = 10.1, para = c(10, 0.1, 0.2))
```

pgpa *Cumulative distribution function of Generalized Pareto Distribution*

Description

Cumulative distribution function of Generalized Pareto Distribution

Usage

```
pgpa(x, para = c(1, 1, 1))
```

Arguments

x	quantile/s
para	parameters as c(location, scale, shape)

Value

Non-exceedance probability from the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
u <- pgpa(x = 1.2, para = c(1, 2, 0.5))
```

pIn3

Cumulative distribution function of Lognormal-3 Distribution

Description

Cumulative distribution function of Lognormal-3 Distribution

Usage

```
pIn3(x, para = c(0, 0, 1))
```

Arguments

x	quantile/s
para	parameters as c(zeta, mu, sigma) that is c(lower bound, mean on log scale, standard deviation on log scale).

Value

Non-exceedance probability from the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
u <- pIn3(x = 12, para = c(0, 0, 1))
```

pnor *Cumulative distribution function of Noramal Distribution*

Description

Cumulative distribution function of Noramal Distribution

Usage

```
pnor(x, para = c(10, 1.5))
```

Arguments

x	quantile/s
para	parameters as c(location, scale)

Value

Non-exceedance probability from the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
u <- pnor(x = 11, para = c(10, 1.5))
```

ppe3 *Cumulative distribution function of Pearson type-3 Distribution*

Description

Cumulative distribution function of Pearson type-3 Distribution

Usage

```
ppe3(x, para = c(10, 1, 1.5))
```

Arguments

x	quantile/s
para	parameters as c(mu, sigma, gamma) that are c(location, scale, shape).

Value

Non-exceedance probability from the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
u <- ppe3(x = 12, para = c(10, 1, 1.5))
```

qBrIII

Quantile distribution function of BrIII distribution

Description

Quantile distribution function of BrIII distribution

Usage

```
qBrIII(u = NULL, RP = 1/(1 - u), para)
```

Arguments

u	non-exceedance probability
RP	Return Period "don't use in case u is used"
para	parameters as c(scale, shape1, shape2)

Value

Quantile value/s using the inverse of the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
x <- qBrIII(u = 0.99, para = c(1, 10, 0.8))
x <- qBrIII(RP = 100, para = c(1, 10, 0.8))
```

`qBrXII`*Quantile distribution function of BrXII distribution*

Description

Quantile distribution function of BrXII distribution

Usage

```
qBrXII(u = NULL, RP = 1/(1 - u), para)
```

Arguments

<code>u</code>	non-exceedance probability
<code>RP</code>	Return Period "don't use in case u is used"
<code>para</code>	parameters as <code>c(scale, shape1, shape2)</code>

Value

Quantile value/s using the inverse of the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
x <- qBrXII(u = 0.99, para = c(1, 10, 0.8))
x <- qBrXII(RP = 100, para = c(1, 10, 0.8))
```

`qgam`*Quantile distribution function of Gamma distribution*

Description

Quantile distribution function of Gamma distribution

Usage

```
qgam(u = NULL, RP = 1/(1 - u), para)
```

Arguments

u	non-exceedance probability
RP	Return Period "don't use in case u is used"
para	parameters as c(shape, scale)

Value

Quantile value/s using the inverse of the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
x <- qgam(u = 0.99, para = c(0.1, 0.2))
x <- qgam(RP = 100, para = c(0.1, 0.2))
```

qgev

Quantile distribution function of GEV distribution

Description

Quantile distribution function of GEV distribution

Usage

```
qgev(u = NULL, RP = 1/(1 - u), para)
```

Arguments

u	non-exceedance probability
RP	Return Period "don't use in case u is used"
para	parameters as c(location, scale, shape)

Value

Quantile value/s using the inverse of the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
x <- qgev(u = 0.99, para = c(10, 1, 1))
x <- qgev(RP = 100, para = c(10, 1, 1))
```

qGG	<i>Quantile distribution function of the Generalized Gamma (GG) distribution</i>
-----	--

Description

Quantile distribution function of the Generalized Gamma (GG) distribution

Usage

```
qGG(u = NULL, RP = 1/(1 - u), para)
```

Arguments

u	non-exceedance probability
RP	Return Period "don't use in case u is used"
para	parameters as c(scale, shape1, shape2)

Value

Quantile value/s using the inverse of the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
x <- qGG(u = 0.99, para = c(10, 0.25, 0.5))
x <- qGG(RP = 100, para = c(10, 0.25, 0.5))
```

qglo

Quantile distribution function of Generalized Logistic Distribution

Description

Quantile distribution function of Generalized Logistic Distribution

Usage

```
qglo(u = NULL, RP = 1/(1 - u), para)
```

Arguments

u	non-exceedance probability
RP	Return Period "don't use in case u is used"
para	parameters as c(location, scale, shape)

Value

Quantile value/s using the inverse of the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
x <- qglo(u = 0.99, para = c(10, 0.1, 0.2))
x <- qglo(RP = 100, para = c(10, 0.1, 0.2))
```

qgno

Quantile distribution function of Generalized normal Distribution

Description

Quantile distribution function of Generalized normal Distribution

Usage

```
qgno(u = NULL, RP = 1/(1 - u), para)
```

Arguments

u	non-exceedance probability
RP	Return Period "don't use in case u is used"
para	parameters as c(location, scale, shape)

Value

Quantile value/s using the inverse of the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
x <- qgno(u = 0.99, para = c(10, 0.1, 0.2))
x <- qgno(RP = 100, para = c(10, 0.1, 0.2))
```

qgpa

Quantile distribution function of Generalized Pareto Distribution

Description

Quantile distribution function of Generalized Pareto Distribution

Usage

```
qgpa(u = NULL, RP = 1/(1 - u), para)
```

Arguments

u	non-exceedance probability
RP	Return Period "don't use in case u is used"
para	parameters as c(location, scale, shape)

Value

Quantile value/s using the inverse of the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
x <- qgpa(u = 0.99, para = c(10, 0.1, 0.2))
x <- qgpa(RP = 100, para = c(10, 0.1, 0.2))
```

qln3*Quantile distribution function of Lognormal-3 Distribution*

Description

Quantile distribution function of Lognormal-3 Distribution

Usage

```
qln3(u = NULL, RP = 1/(1 - u), para)
```

Arguments

u	non-exceedance probability
RP	Return Period "don't use in case u is used"
para	parameters as c(zeta, mu, sigma) that is c(lower bound, mean on log scale, standard deviation on log scale).

Value

Quantile value/s using the inverse of the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
x <- qln3(u = 0.99, para = c(0, 0, 1))
x <- qln3(RP = 100, para = c(0, 0, 1))
```

qnor *Quantile distribution function of Normal Distribution*

Description

Quantile distribution function of Normal Distribution

Usage

```
qnor(u = NULL, RP = 1/(1 - u), para)
```

Arguments

u	non-exceedance probability
RP	Return Period "don't use in case u is used"
para	parameters as c(location, scale)

Value

Quantile value/s using the inverse of the cumulative distribution function.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
x <- qnor(u = 0.99, para = c(10, 0.1))  
x <- qnor(RP = 100, para = c(10, 0.1))
```

qpe3 *Quantile distribution function of Pearson type-3 Distribution*

Description

Quantile distribution function of Pearson type-3 Distribution

Usage

```
qpe3(u = NULL, RP = 1/(1 - u), para)
```

Arguments

u	non-exceedance probability
RP	Return Period "don't use in case u is used"
para	parameters as c(mu, sigma, gamma) that is c(location, scale, shape).

Value

Quantile value/s using the inverse of the cumulative distribution function.

Author(s)

Mohanad Zaghloul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
x <- qpe3(u = 0.99, para = c(1, 1, 0))
x <- qpe3(RP = 100, para = c(1, 1, 0))
```

tBrIII

Return period function of BrIII distribution

Description

Return period function of BrIII distribution

Usage

```
tBrIII(x, para = c(1, 2, 0.5))
```

Arguments

x	quantile/s
para	parameters as c(scale, shape1, shape2)

Value

Return Period/s corresponding to quantile/s.

Author(s)

Mohanad Zaghloul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
RP <- tBrIII(x = 108.4992, para = c(10, 0.25, 0.5))
```

tBrXII *Return period function of BrXII distribution*

Description

Return period function of BrXII distribution

Usage

```
tBrXII(x, para = c(1, 2, 0.5))
```

Arguments

x	quantile/s
para	parameters as c(scale, shape1, shape2)

Value

Return Period/s corresponding to quantile/s.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
RP <- tBrXII(x = 108.4992, para = c(10, 0.25, 0.5))
```

tgam *Return period function of Gamma distribution*

Description

Return period function of Gamma distribution

Usage

```
tgam(x, para = c(1.5, 1))
```

Arguments

x	quantile/s
para	parameters as c(shape, scale)

Value

Return Period/s corresponding to quantile/s.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
RP <- tgam(x = 0.1, para = c(0.1, 0.2))
```

tgev

Return period function of GEV distribution

Description

Return period function of GEV distribution

Usage

```
tgev(x, para)
```

Arguments

x	quantile/s
para	parameters as c(location, scale, shape)

Value

Return Period/s corresponding to quantile/s.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
RP <- tgev(x = 108.4992, para = c(10, 1, 1))
```

tGG *Return period function of Generalized Gamma distribution*

Description

Return period function of Generalized Gamma distribution

Usage

```
tGG(x, para = c(10, 0.25, 0.5))
```

Arguments

x	quantile/s
para	parameters as c(scale, shape1, shape2)

Value

Return Period/s corresponding to quantile/s.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
RP <- tGG(x = 108.4992, para = c(10, 0.25, 0.5))
```

tglo *Return period function of Generalized Logistic distribution*

Description

Return period function of Generalized Logistic distribution

Usage

```
tglo(x, para = c(10, 1.5, 1))
```

Arguments

x	quantile/s
para	parameters as c(location, scale, shape)

Value

Return Period/s corresponding to quantile/s.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
RP <- tglo(x = 0.1, para = c(10, 0.1, 0.2))
```

tgno

Return period function of Generalized Normal distribution

Description

Return period function of Generalized Normal distribution

Usage

```
tgno(x, para = c(10, 1.5, 1))
```

Arguments

x	quantile/s
para	parameters as c(location, scale, shape)

Value

Return Period/s corresponding to quantile/s.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
RP <- tgno(x = 10.1, para = c(10, 0.1, 0.2))
```

tgpa *Return period function of Generalized Pareto distribution*

Description

Return period function of Generalized Pareto distribution

Usage

```
tgpa(x, para = c(1, 1, 1))
```

Arguments

x	quantile/s
para	parameters as c(location, scale, shape)

Value

Return Period/s corresponding to quantile/s.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
RP <- tgpa(x = 1.2, para = c(1, 2, 0.5))
```

tln3 *Return period function of Lognormal-3 distribution*

Description

Return period function of Lognormal-3 distribution

Usage

```
tln3(x, para = c(0, 0, 1))
```

Arguments

x	quantile/s
para	parameters as c(zeta, mu, sigma) that is c(lower bound, mean on log scale, standard deviation on log scale).

Value

Return Period/s corresponding to quantile/s.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
RP <- tln3(x = 12, para = c(0, 0, 1))
```

tnor

Return period function of Noramal distribution

Description

Return period function of Noramal distribution

Usage

```
tnor(x, para = c(10, 1.5))
```

Arguments

x	quantile/s
para	parameters as c(location, scale)

Value

Return Period/s corresponding to quantile/s.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
RP <- tnor(x = 11, para = c(10, 1.5))
```

tpe3

Return period function of Pearson type-3 distribution

Description

Return period function of Pearson type-3 distribution

Usage

```
tpe3(x, para = c(10, 1, 1.5))
```

Arguments

x	quantile/s
para	parameters as c(mu, sigma, gamma) that are c(location, scale, shape).

Value

Return Period/s corresponding to quantile/s.

Author(s)

Mohanad Zaghoul [aut, cre], Simon Michael Papalexiou [aut, ths], Amin Elshorbagy [aut, ths]

Examples

```
RP <- tpe3(x = 12, para = c(10, 1, 1.5))
```

Index

* datasets

FLOW_AMAX, 21
FLOW_AMAX_MULT, 22
lspace_BrIII, 24
lspace_BrIII.xy, 25
lspace_BrXII, 25
lspace_BrXII.xy, 26
lspace_GG, 27
lspace_GG.xy, 27

com_sam_lspace, 3
con_sam_lspace, 5
con_samlmom_lspace, 4

dBrIII, 6
dBrXII, 7
dgam, 7
dgev, 8
dGG, 9
dglo, 9
dgno, 10
dgpa, 11
dln3, 11
dnor, 12
dpe3, 13

fit_BrIII, 13
fit_BrXII, 14
fit_gam, 15
fit_gev, 15
fit_GG, 16
fit_glo, 17
fit_gno, 18
fit_gpa, 18
fit_ln3, 19
fit_nor, 20
fit_pe3, 21
FLOW_AMAX, 21
FLOW_AMAX_MULT, 22
get_julian, 23
get_sample_lmom, 23
lspace_BrIII, 24
lspace_BrIII.xy, 25
lspace_BrXII, 25
lspace_BrXII.xy, 26
lspace_GG, 27
lspace_GG.xy, 27

pBrIII, 28
pBrXII, 29
pemp, 29
pgam, 30
pgev, 31
pGG, 31
pglo, 32
pgno, 33
pgpa, 33
pln3, 34
pnor, 35
ppe3, 35

qBrIII, 36
qBrXII, 37
qgam, 37
qgev, 38
qGG, 39
qglo, 40
qgno, 40
qgpa, 41
qln3, 42
qnor, 43
qpe3, 43

tBrIII, 44
tBrXII, 45
tgam, 45
tgev, 46
tGG, 47
tglo, 47

tgn0, 48
tgpa, 49
tln3, 49
tnor, 50
tpe3, 51