

Package ‘Rdiagnosislist’

April 18, 2023

Title Manipulate SNOMED CT Diagnosis Lists

Version 1.2

Description Functions and methods for manipulating 'SNOMED CT' concepts. The package contains functions for loading the 'SNOMED CT' release into a convenient R environment, selecting 'SNOMED CT' concepts using regular expressions, and navigating the 'SNOMED CT' ontology. It provides the 'SNOMEDconcept' S3 class for a vector of 'SNOMED CT' concepts (stored as 64-bit integers) and the 'SNOMEDcodelist' S3 class for a table of concepts IDs with descriptions. For more information about 'SNOMED CT' visit <<https://www.snomed.org/>>.

License GPL-3

Imports data.table, bit64, methods

Suggests knitr, rmarkdown, testthat

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

Author Anoop Shah [aut, cre] (<<https://orcid.org/0000-0002-8907-5724>>)

Maintainer Anoop Shah <anoop@doctors.org.uk>

VignetteBuilder knitr

NeedsCompilation no

Depends R (>= 3.5.0)

Repository CRAN

Date/Publication 2023-04-18 11:40:05 UTC

R topics documented:

addInactiveConcepts	2
as.data.frame.SNOMEDconcept	3
attrConcept	4
c.SNOMEDconcept	5
createSNOMEDindices	6

description	6
expandSNOMED	7
export	9
exportSNOMEDenvir	9
getMaps	10
getRefset	12
getSNOMED	12
hasAttributes	13
HISTORY	14
htmlCodelistHierarchy	15
inactiveIncluded	16
is.SNOMEDcodelist	17
is.SNOMEDconcept	18
loadREADMAPS	19
loadSNOMED	20
parents	21
print.SNOMEDcodelist	22
print.SNOMEDconcept	23
QUERY	23
Rdiagnosislist	24
READMAPS	24
relatedConcepts	25
sampleSNOMED	26
semanticType	27
simplify	28
SNOMEDcodelist	29
SNOMED_CONCEPT	31
SNOMED_DESCRIPTION	31
SNOMED_EXTENDEDMAP	32
SNOMED_REFSET	33
SNOMED_RELATIONSHIP	34
SNOMED_SIMPLEMAP	35
union.SNOMEDconcept	36
unique.SNOMEDconcept	38

Index **39**

addInactiveConcepts	<i>Add inactive concepts to a SNOMEDcodelist or SNOMEDconcept vector</i>
---------------------	--

Description

Adds SNOMED concepts linked by the QUERY or HISTORY tables that are mapped to or descendants of concepts in a SNOMEDcodelist or a SNOMEDconcept vector. If a SNOMEDcodelist, it is automatically converted to the 'simple' format (all items enumerated).

Usage

```
addInactiveConcepts(x, provenance = 0:3, SNOMED = getSNOMED())
```

Arguments

x	SNOMEDcodelist or SNOMEDconcept object
provenance	vector of provenance values to use
SNOMED	SNOMED environment containing HISTORY and QUERY tables

Details

It is recommended to use this function to convert a reference into a codelist for running a query against an electronic health record database which might contain historic SNOMED CT concepts.

Value

SNOMEDcodelist or SNOMEDconcept with linked inactive concepts included

See Also

Other SNOMEDcodelist functions: [SNOMEDcodelist\(\)](#), [expandSNOMED\(\)](#), [export\(\)](#), [is.SNOMEDcodelist\(\)](#), [print.SNOMEDcodelist\(\)](#)

```
as.data.frame.SNOMEDconcept
```

Returns the SNOMED CT concept IDs for a set of terms

Description

Carries out an exact or regular expression match to return the concept ID for a set of search terms, or converts a character, integer or integer64 vector to a SNOMEDconcept object.

Usage

```
## S3 method for class 'SNOMEDconcept'
as.data.frame(x, ...)

## S3 method for class 'SNOMEDconcept'
as.integer64(x, ...)

SNOMEDconcept(
  x,
  active_only = TRUE,
  exact_match = TRUE,
  unique = TRUE,
  SNOMED = getSNOMED()
)
```

```
as.SNOMEDconcept(x, ...)
```

Arguments

x	character vector of terms to match, or character vector containing SNOMED CT concept IDs, or 64-bit integer vector containing SNOMED CT concept IDs
...	additional arguments to send to grepl if using regular expression matching
active_only	whether or not to include inactive concepts
exact_match	if TRUE, only an exact (case sensitive) match is performed. If FALSE, a regular expression match is performed.
unique	whether to include no more than one instance of each SNOMED CT concept
SNOMED	environment containing SNOMED dictionary. Defaults to an object named 'SNOMED' in the global environment

Value

a SNOMEDconcept object (vector of 64-bit integers) containing unique SNOMED CT concept IDs

See Also

Other SNOMEDconcept functions: [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [union.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

Other SNOMEDconcept functions: [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [union.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

Other SNOMEDconcept functions: [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [union.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

Examples

```
SNOMEDconcept('Heart failure', SNOMED = sampleSNOMED()) -> hf
is.SNOMEDconcept(hf)
SNOMEDconcept('900000000000003001')
as.SNOMEDconcept('900000000000003001')
```

attrConcept

Retrieve all attributes of a set of SNOMED CT concepts

Description

Returns the portion of the SNOMED CT relationship tables containing relationships where the given concepts are either the source or the destination.

Usage

```
attrConcept(
  conceptIds,
  SNOMED = getSNOMED(),
  tables = c("RELATIONSHIP", "STATEDRELATIONSHIP"),
  active_only = TRUE
)
```

Arguments

conceptIds	character or integer64 vector of SNOMED concept IDs
SNOMED	environment containing a SNOMED dictionary
tables	character vector of relationship tables to use
active_only	whether to return only active attributes

Value

a data.table with the following columns: sourceId (concept ID of source for relationship), destinationId (concept ID of source for relationship), typeId (concept ID of relationship type), typeName (description of relationship type)

Examples

```
SNOMED <- sampleSNOMED()

attrConcept(as.SNOMEDconcept('Heart failure'))
```

c.SNOMEDconcept	<i>Concatenate vectors of SNOMED CT concepts</i>
-----------------	--

Description

SNOMEDconcept is an S3 class for vectors of SNOMED concept IDs as 64-bit integers. This function concatenates two or more SNOMEDconcept vectors.

Usage

```
## S3 method for class 'SNOMEDconcept'
c(...)
```

Arguments

...	SNOMEDconcept vectors
-----	-----------------------

Value

concatenation of vectors

See Also

Other SNOMEDconcept functions: [as.data.frame.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [union.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

Examples

```
hf <- SNOMEDconcept('Heart failure', SNOMED = sampleSNOMED())
hf2 <- c(hf, hf)
```

`createSNOMEDindices` *Create indices for tables in a SNOMED environment*

Description

Creates relevant indices for fast searching of SNOMED CT tables

Usage

```
createSNOMEDindices(SNOMED)
```

Arguments

SNOMED environment containing data.table objects: CONCEPT, DESCRIPTION, RELATIONSHIP, STATEDRELATIONSHIP

Value

The environment with indices added to each table for fast searching

See Also

CONCEPT, DESCRIPTION, RELATIONSHIP, STATEDRELATIONSHIP, REFSET, SIMPLEMAP, EXTENDEDMAP, loadSNOMED, sampleSNOMED

`description` *Obtain descriptions for a set of SNOMED CT terms*

Description

Returns the descriptions matching a set of concept IDs from a SNOMED dictionary

Usage

```
description(
  conceptIds,
  include_synonyms = FALSE,
  active_only = TRUE,
  SNOMED = getSNOMED()
)
```

Arguments

conceptIds character or integer64 vector

include_synonyms whether to return only the Fully Specified Name (default) or all synonyms

active_only whether to include only active descriptions

SNOMED environment containing SNOMED dictionary. Defaults to an object named 'SNOMED' in the global environment

Value

a data.table with the following columns: id, conceptId, type (only if include_synonyms = TRUE), term, active (only if active_only = FALSE)

Examples

```
hf <- SNOMEDconcept('Heart failure', SNOMED = sampleSNOMED())
description(hf, include_synonyms = FALSE, SNOMED = sampleSNOMED())
```

expandSNOMED	<i>Expand or contract a SNOMEDcodelist</i>
--------------	--

Description

SNOMEDcodelist is an S3 class for sets of SNOMED concepts. In the 'contracted' form, it may contain only parents and not child terms (to create a more succinct list). The 'Expanded' form contains all concepts. The output of 'showCodelistHierarchy' includes all hierarchies contained within the codelist in a format suitable for display.

Usage

```
expandSNOMED(x, SNOMED = getSNOMED(), ...)

contractSNOMED(x, SNOMED = getSNOMED(), ...)

showCodelistHierarchy(
  x,
  SNOMED = getSNOMED(),
```

```

    max_excluded_descendants = 200,
    ...
)

```

Arguments

x	SNOMEDcodelist to expand or contract. If x is not a SNOMEDcodelist, it is coerced to one by <code>as.SNOMEDcodelist</code>
SNOMED	environment containing a SNOMED dictionary
...	other arguments to pass to <code>as.SNOMEDcodelist</code>
max_excluded_descendants	(integer) whether to show excluded descendants as long as they do not exceed this number (a limit is suggested to avoid the program crashing if there are too many descendants). If this number is exceeded, the program will initially try to include children only, and if there are still too many, it will ignore all descendants. An 'included' column is added to the codelist showing which terms are included. This can make it easy to see if a codelist is consistent with the SNOMED CT ontology.

Value

An object of class 'SNOMEDcodelist' with attribute `Expanded = TRUE`

See Also

Other SNOMEDcodelist functions: [SNOMEDcodelist\(\)](#), [addInactiveConcepts\(\)](#), [export\(\)](#), [is.SNOMEDcodelist\(\)](#), [print.SNOMEDcodelist\(\)](#)

Other SNOMEDcodelist functions: [SNOMEDcodelist\(\)](#), [addInactiveConcepts\(\)](#), [export\(\)](#), [is.SNOMEDcodelist\(\)](#), [print.SNOMEDcodelist\(\)](#)

Other SNOMEDcodelist functions: [SNOMEDcodelist\(\)](#), [addInactiveConcepts\(\)](#), [export\(\)](#), [is.SNOMEDcodelist\(\)](#), [print.SNOMEDcodelist\(\)](#)

Examples

```

SNOMED <- sampleSNOMED()

my_concepts <- SNOMEDconcept('Heart failure')
my_codelist <- SNOMEDcodelist(data.frame(conceptId = my_concepts,
  include_desc = TRUE))
expanded_codelist <- expandSNOMED(my_codelist)
contractSNOMED(expanded_codelist)

```

export	<i>Export a SNOMEDcodelist</i>
--------	--------------------------------

Description

Writes a SNOMEDcodelist to file. If the filename is NULL, a filename is created from the 'codelist_name' attribute.

Usage

```
export(x, ...)
```

```
## S3 method for class 'SNOMEDcodelist'
export(x, filename = NULL, ...)
```

Arguments

x	SNOMEDcodelist object to export to file
...	not used
filename	character vector of length 1 for the file to write to. If NULL, a filename is generated from the codelist filename.

Value

invisibly returns the exported codelist

See Also

Other SNOMEDcodelist functions: [SNOMEDcodelist\(\)](#), [addInactiveConcepts\(\)](#), [expandSNOMED\(\)](#), [is.SNOMEDcodelist\(\)](#), [print.SNOMEDcodelist\(\)](#)

Other SNOMEDcodelist functions: [SNOMEDcodelist\(\)](#), [addInactiveConcepts\(\)](#), [expandSNOMED\(\)](#), [is.SNOMEDcodelist\(\)](#), [print.SNOMEDcodelist\(\)](#)

exportSNOMEDenvir	<i>Export a SNOMED environment to a folder</i>
-------------------	--

Description

Creates tab separated files which can be reloaded with relevant indices for fast searching of SNOMED CT tables

Usage

```
exportSNOMEDenvir(SNOMED, folder)
```

Arguments

SNOMED	environment containing data.table objects: CONCEPT, DESCRIPTION, RELATIONSHIP, STATEDRELATIONSHIP, REFSET, SIMPLEMAP, EXTENDEDMAP
folder	path to folder where files will be written

See Also

CONCEPT, DESCRIPTION, RELATIONSHIP, STATEDRELATIONSHIP

getMaps	<i>Obtain Read 2, CTV3, ICD-10 and OPCS4 maps for SNOMED CT concepts</i>
---------	--

Description

Returns concepts mapped to SNOMED CT from either the SIMPLEMAP table in the SNOMED dictionary (Clinical Terms Version 3, CTV3 maps, one per concept), the EXTENDEDMAP table (ICD-10 and OPCS4 maps) or a separate mapping table with Read Clinical Terms Version 2 (Read 2) and CTV3 maps. A sample mapping table (READMAPS) is provided.

Usage

```
getMaps(
  x,
  mappingtable = NULL,
  to = c("read2", "ctv3", "icd10", "opcs4", "ctv3simple"),
  SNOMED = getSNOMED(),
  single_row_per_concept = TRUE
)
```

Arguments

x	SNOMEDcodelist or SNOMEDconcept object. If it is a SNOMEDconcept object it is first converted to a SNOMEDcodelist. If it is a SNOMEDcodelist it is first converted to 'simple' format. Columns named 'read2_code' or 'read2_term' (if adding Read 2 maps) or 'ctv3_concept' or 'ctv3_termid' (if adding CTV3 maps) will be overwritten.
mappingtable	data.table containing mapping in the format described in 'Details'. The MAPS dataset in this package provides a sample. It must contain a unique field 'conceptId', and fields named 'read2_code' and 'read2_term' (for mapping to Read 2) or 'ctv3_concept' and 'ctv3_termid' (for mapping to CTV3).
to	character vector stating which terminologies to map to. Options are 'icd10', 'opcs4', 'ctv3simple' (use tables included within the SNOMED dictionary), or 'read2' or 'ctv3' (require a separate mapping table such as READMAPS). Beware that including multiple destination terminologies may result in a significant expansion of the number of rows if single_row_per_concept is FALSE.

SNOMED an environment containing the SNOMED CT dictionary. If not supplied, it will be obtained using `getSNOMED()`.

single_row_per_concept (logical) if TRUE (default), the function returns a single row per concept with Read 2 and CTV3 maps returned as lists (i.e. multiple entries within a single cell). This means the output is a valid `SNOMEDcodelist` object. If FALSE, returns multiple rows per concept (one for each map).

Details

The mapping table can be created from the NHS Digital 'Data Migration' pack files which contain 'forward' maps of Read 2 and CTV3 to SNOMED CT. These are intended for converting individual entries in electronic health records to SNOMED CT. The 'forward' map files contain a SNOMED CT map for every Read 2 or CTV3 code, but not all the SNOMED CT concepts are mapped. Future SNOMED CT concepts will also not be mapped.

These maps can be used for converting SNOMED CT codelists into Read 2 or CTV3 format for running queries, such as to characterise patient phenotypes or identify patient populations for research. They cannot be used in the reverse direction (to map a Read 2/CTV3 codelist to SNOMED CT) because some of the SNOMED CT terms will be missed out, and the list will be incomplete.

The mapping table must be a `data.table` object with columns: `conceptId` (integer64, unique), `read2_code` (character list of 7-character Read 2 codes), `read2_term` (character list of Read 2 terms), `ctv3_concept` (character list of CTV3 concept codes), `ctv3_termid` (character list of CTV3 term description codes)

Value

a `data.table` containing the columns `conceptId` and either `'read2_code'` and `'read2_term'` (for mapping to Read 2), `'ctv3_concept'` and `'ctv3_termid'` (for mapping to CTV3 using the mapping table), `'ctv3_simple'` (mapping to CTV3 using `SIMPLEMAP` within the SNOMED dictionary), `'icd10_code'` or `'opcs4_code'` (mapped using `EXTENDEDMAP` within the SNOMED dictionary). If `single_row_per_concept` is TRUE, the mapped rows are of type 'list' and the output is also a `SNOMEDcodelist` in 'simple' format, otherwise the output may have multiple rows per `conceptId`. Note that each Read 2, CTV3, ICD-10 or OPCS4 term may be mapped to multiple SNOMED CT concepts.

See Also

`READMAPS`, `loadREADMAPS`

Examples

```
# Load sample SNOMED CT dictionary into the global environment
# so it is available to the functions in this example
SNOMED <- sampleSNOMED()
# Use the sample READMAPS table in this package
data(READMAPS)

# Example: Mapping a single concept
getMaps(SNOMEDconcept('Heart failure'), mappingtable = READMAPS,
        to = 'read2')
```

```
# Example: Mapping a concept and its descendants
getMaps(descendants(SNOMEDconcept('Heart failure')),
  mappingtable = READMAPS, to = 'read2')
# Example: Mapping a codelist
getMaps(SNOMEDcodelist(SNOMEDconcept('Heart failure')),
  mappingtable = READMAPS, to = c('ctv3', 'ctv3simple', 'icd10'))
```

getRefset *Retrieves a Refset from the REFSET table*

Description

Retrieves a Refset from the REFSET table

Usage

```
getRefset(conceptIds, SNOMED = getSNOMED())
```

Arguments

conceptIds	character or integer64 vector of Refset SNOMED concept IDs, or something that can be coerced to a SNOMEDconcept
SNOMED	environment containing a SNOMED dictionary

Value

a SNOMEDconcept vector of conceptIds of members of the selected refset(s)

Examples

```
SNOMED <- sampleSNOMED()

getRefset(c('Renal clinical finding simple reference set',
  'Care planning activities simple reference set'))
```

getSNOMED *Retrieves SNOMED CT dictionary from the global environment*

Description

Returns an object named 'SNOMED' from the global environment. Returns an error if no such object exists, or if it is not an environment containing tables named CONCEPT, RELATIONSHIP, STATEDRELATIONSHIP and DESCRIPTION. There is no attempt to check that these tables are actually valid.

Usage

```
getSNOMED(SNOMEDname = "SNOMED")
```

Arguments

SNOMEDname name of the SNOMED environment to search for

Value

SNOMED environment from the global environment

See Also

CONCEPT, DESCRIPTION, RELATIONSHIP, STATEDRELATIONSHIP, REFSET, SIMPLEMAP, EXTENDEDMAP, loadSNOMED, sampleSNOMED

Examples

```
SNOMED <- sampleSNOMED()
SNOMED2 <- getSNOMED()

# To display metadata for this SNOMED CT dictionary
SNOMED2$metadata
```

hasAttributes	<i>Whether SNOMED CT concepts have particular attributes</i>
---------------	--

Description

For each concept in the first list, whether it has the attribute in the second list. Returns a vector of Booleans.

Usage

```
hasAttributes(
  sourceIds,
  destinationIds,
  typeId = bit64::as.integer64("116680003"),
  SNOMED = getSNOMED(),
  tables = c("RELATIONSHIP", "STATEDRELATIONSHIP"),
  active_only = TRUE
)
```

Arguments

sourceIds	character or integer64 vector of SNOMED concept IDs for children, recycled if necessary
destinationIds	character or integer64 vector of SNOMED concept IDs for parents, recycled if necessary
typeIds	character or integer64 vector of SNOMED concept IDs for relationship types, recycled if necessary. Defaults to 116680003 = 'Is a' (child/parent)
SNOMED	environment containing a SNOMED dictionary
tables	character vector of relationship tables to use
active_only	whether only active relationships should be considered, default TRUE

Value

a vector of Booleans stating whether the attribute exists

Examples

```
SNOMED <- sampleSNOMED()

hasAttributes(c('Heart failure', 'Acute heart failure'),
             c('Heart structure', 'Heart failure'),
             c('Finding site', 'Is a'))
```

HISTORY

Sample history substitution table from SNOMED CT dictionary

Description

Sample of the SNOMED CT table showing current equivalents for inactive concepts.

Usage

```
data(HISTORY)
```

Format

An object of class "data.table"

Details

- OLDCONCEPTID integer64: concept ID of the inactive concepts
- OLDCONCEPTSTATUS integer: status of the old concept
- NEWCONCEPTID integer64: concept ID of the new concept
- NEWCONCEPTSTATUS integer: status of the new concept
- PATH character: path

- ISAMBIGUOUS integer: whether ambiguous
- ITERATIONS integer: number of iterations
- OLDCONCEPTFSN character: old concept Fully Specified Name
- OLDCONCEPTFSN_TAGCOUNT integer: number of tags for old concept
- NEWCONCEPTFSN integer: new concept Fully Specified Name
- NEWCONCEPTFSN_STATUS integer: new concept Fully Specified Name status
- TLH_IDENTICALFLAG integer: whether TLH identical
- FSN_TAGLESSIDENTICALFLAG integer: whether Fully Specified Names are identical ignoring the tags
- FSN_TAGIDENTICALFLAG integer: whether Fully Specified Names tags are identical

See Also

Other SNOMEDsample: [QUERY](#), [SNOMED_RELATIONSHIP](#)

Examples

```
# Create a TEST environment and load the sample dictionaries
TEST <- new.env()
data(CONCEPT, envir = TEST)
data(DESCRIPTION, envir = TEST)
data(RELATIONSHIP, envir = TEST)
data(STATEDRELATIONSHIP, envir = TEST)
data(HISTORY, envir = TEST)

# Show properties of the history table
str(TEST$HISTORY)
```

htmlCodelistHierarchy *Export a SNOMEDcodelist hierarchy to HTML*

Description

Exports a codelist with hierarchy as HTML for easy viewing.

Usage

```
htmlCodelistHierarchy(
  x,
  file = NULL,
  title = NULL,
  description = NULL,
  extracols = NULL,
  SNOMED = getSNOMED(),
  ...
)
```

Arguments

<code>x</code>	a <code>SNOMEDcodelist</code> , <code>codelistHierarchy</code> (output of <code>showCodelistHierarchy</code>), or an object which can be coerced to a <code>SNOMEDcodelist</code> (such as a <code>SNOMED-concept</code> vector).
<code>file</code>	filename to export to. If <code>NULL</code> , no file is written
<code>title</code>	title of HTML document
<code>description</code>	paragraph of description text (excluding <code><p></p></code> tags)
<code>extracols</code>	character vector of additional columns of <code>codelist_with_hierarchy</code> to include in HTML output
<code>SNOMED</code>	environment containing the SNOMED dictionary to use
<code>...</code>	extra arguments to pass to <code>as.SNOMEDcodelist</code>

Value

a character vector containing HTML output

See Also

`showCodelistHierarchy`

Examples

```
SNOMED <- sampleSNOMED()

my_concepts <- SNOMEDconcept('Acute heart failure')
my_codelist <- SNOMEDcodelist(data.frame(conceptId = my_concepts,
  include_desc = TRUE))
htmlCodelistHierarchy(my_codelist, file = paste0(tempdir(),
  'codelist.html'))
# The codelist.html file can now be viewed in a web browser

# Clean up temporary file
file.remove(paste0(tempdir(), 'codelist.html'))
```

<code>inactiveIncluded</code>	<i>Check if inactive terms are included in SNOMED CT dictionary</i>
-------------------------------	---

Description

Checks the `active_only` flag in the metadata of a SNOMED environment to determine whether inactive terms are included

Usage

```
inactiveIncluded(SNOMED = getSNOMED())
```

Arguments

SNOMED environment containing SNOMED dictionary, defaults to an object named 'SNOMED' in the global environment

Value

TRUE or FALSE (logical vector of length one)

Examples

```
# Create a TEST environment and load the sample dictionaries
TEST <- sampleSNOMED()
inactiveIncluded(TEST)
assign('metadata', list(active_only = TRUE), envir = TEST)
inactiveIncluded(TEST)
```

is.SNOMEDcodelist *Check if an object is a SNOMEDcodelist*

Description

SNOMEDcodelist is an S3 class for lists of SNOMED codes. This function checks whether the object has the class SNOMEDcodelist, and whether the specified attributes are as per the arguments (if the arguments are left as NULL, as per default, they are not checked). The function does not check if the codelist contains valid data.

Usage

```
is.SNOMEDcodelist(
  x,
  format = NULL,
  codelist_name = NULL,
  version = NULL,
  author = NULL,
  date = NULL,
  SNOMED = NULL
)
```

Arguments

x object to check

format Whether the codelist is expressed as a simple enumeration of concepts ('simple'), as a set of concept hierarchies ('tree') or as a set of hierarchies showing all concepts ('exptree'). Codelists can be converted between the formats, but the result of conversion may depend on the SNOMED CT dictionary being used.

codelist_name Name of the codelist (character vector of length 1)

version Version of the codelist (character vector of length 1)

author	Author of the codelist (character vector of length 1)
date	Date assigned to the codelist (character vector of length 1)
SNOMED	Dummy argument to ensure that this function works with <code>as.SNOMEDcodelist</code>

Value

a logical vector of length one: TRUE or FALSE

See Also

Other SNOMEDcodelist functions: [SNOMEDcodelist\(\)](#), [addInactiveConcepts\(\)](#), [expandSNOMED\(\)](#), [export\(\)](#), [print.SNOMEDcodelist\(\)](#)

<code>is.SNOMEDconcept</code>	<i>Check if an object is a SNOMEDconcept</i>
-------------------------------	--

Description

SNOMEDconcept is an S3 class for vectors of SNOMED concept IDs as 64-bit integers. This function checks whether the object has the class SNOMEDconcept and is a vector of 64-bit integers.

Usage

```
is.SNOMEDconcept(x)
```

Arguments

x	object to check
---	-----------------

Value

a logical vector of length one: TRUE or FALSE

See Also

Other SNOMEDconcept functions: [as.data.frame.SNOMEDconcept\(\)](#), [c.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [union.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

`loadREADMAPS`*Load mappings from Read to SNOMED CT into an R data.table*

Description

Creates a mapping table derived from NHS Digital Data Migration distribution. These tables are available from the Technology Reference Update Distribution: <https://isd.digital.nhs.uk/trud/user/guest/group/0/pack/9/subpack/9/releases>

Usage

```
loadREADMAPS(  
  not_assured_rcsctmap_uk,  
  not_assured_rctermstmap_uk,  
  assured_ctv3sctmap2_uk  
)
```

Arguments

`not_assured_rcsctmap_uk`
File containing Read 2 codes mapped to SNOMED CT, in file: 'Not Clinically Assured/rcsctmap_uk_20200401000001.txt'

`not_assured_rctermstmap_uk`
File containing Read 2 terms mapped to SNOMED CT, in file: 'Not Clinically Assured/rctermstmap_uk_20200401000001.txt'

`assured_ctv3sctmap2_uk`
File containing CTV3 concepts and terms mapped to SNOMED CT, in file: 'Clinically Assured/ctv3sctmap2_uk_20200401000001.txt'

Details

The final release was in April 2020. The mapping tables are intended for converting entire in clinical records from Read Version 2 (Read 2) to SNOMED CT, and Clinical Terms Version 3 (CTV3) to SNOMED CT.

These maps can be used for converting SNOMED CT codelists into Read 2 or CTV3 format for running queries, such as to characterise patient phenotypes or identify patient populations for research. They cannot be used in the reverse direction (to map a Read 2/CTV3 codelist to SNOMED CT) because some of the SNOMED CT terms will be missed out, and the list will be incomplete.

This function uses the following three mapping files:

- `not_assured_rcsctmap_uk` File containing Read 2 codes mapped to SNOMED CT, in file: 'Not Clinically Assured/rcsctmap_uk_20200401000001.txt'
- `not_assured_rctermstmap_uk` File containing Read 2 terms mapped to SNOMED CT, in file: 'Not Clinically Assured/rctermstmap_uk_20200401000001.txt'
- `assured_ctv3sctmap2_uk` File containing CTV3 concepts and terms mapped to SNOMED CT, in file: 'Clinically Assured/ctv3sctmap2_uk_20200401000001.txt'

The output `data.table` has the following columns:

- `conceptId` integer64: SNOMED CT `conceptId` (primary key)
- `read2_code` list: character list of 7-character Read 2 codes
- `read2_term` list: character list of Read 2 terms
- `ctv3_concept` list: character list of CTV3 concept codes
- `ctv3_termid` list: character list of CTV3 term description codes

Value

A `data.table` with columns `conceptId`, `read2_code`, `ctv3_concept`, `ctv3_termid`

See Also

READMAPS, `getMaps`, `loadSNOMED`

loadSNOMED

Load SNOMED CT files from a folder(s) into R data.table objects

Description

Identifies relevant SNOMED CT files from the folder structure of a SNOMED CT distribution. This includes the core 'Snapshot' tables mapping tables from the 'Refset' folder and the history substitution table and query table. The relevant tables are loaded into an R environment, which can be saved and then easily retrieved for future use. Files from two folders (e.g. International and UK versions) can be loaded together, and are automatically appended by the function.

Usage

```
loadSNOMED(folders, active_only = TRUE, version = NULL)
```

Arguments

<code>folders</code>	Vector of folder paths containing SNOMED CT files
<code>active_only</code>	Whether to limit to current (active) SNOMED CT concepts
<code>version</code>	Version description. If NULL, it is derived from the folder paths and expressed in the form: INTdate & UKdate

Details

The SNOMED CT files are available from the NHS Digital Technology Reference Update Distribution: <https://isd.digital.nhs.uk/trud/user/guest/group/0/home>

(Note: May 2022 - This function needs to be updated to use the latest SNOMED CT TRUD versions including the SNOMED CT definitions).

Value

An environment containing data.table objects: CONCEPT, DESCRIPTION, RELATIONSHIP, STATEDRELATIONSHIP, REFSET, SIMPLEMAP, EXTENDEDMAP, HISTORY (optional), QUERY (optional)

See Also

loadREADMAPS, CONCEPT, DESCRIPTION, RELATIONSHIP, STATEDRELATIONSHIP, REFSET, SIMPLEMAP, EXTENDEDMAP, QUERY, HISTORY sampleSNOMED, getSNOMED, exportSNOMEDenvir

Examples

```
# Create a TEST environment and load the sample dictionaries
TEST <- sampleSNOMED()

# Export to temporary directory
exportSNOMEDenvir(TEST, tempdir())

# Try to import using the loadSNOMED function
TEST2 <- loadSNOMED(tempdir(), active_only = FALSE)

# Check that reimported SNOMED dictionary is the same as the original
all.equal(TEST$CONCEPT, TEST2$CONCEPT)
all.equal(TEST$DESCRIPTION, TEST2$DESCRIPTION)
all.equal(TEST$RELATIONSHIP, TEST2$RELATIONSHIP)
all.equal(TEST$STATEDRELATIONSHIP, TEST2$STATEDRELATIONSHIP)
all.equal(TEST$REFSET, TEST2$REFSET)
all.equal(TEST$SIMPLEMAP, TEST2$SIMPLEMAP)
all.equal(TEST$EXTENDEDMAP, TEST2$EXTENDEDMAP)
```

 parents

Ancestors and descendants of SNOMED CT concepts

Description

Returns concepts with 'Is a' or inverse 'Is a' relationship with a set of target concepts. Ancestors include parents and all higher relations. Descendants include children and all lower relations.

Usage

```
parents(conceptIds, include_self = FALSE, SNOMED = getSNOMED(), ...)
```

```
ancestors(conceptIds, include_self = FALSE, SNOMED = getSNOMED(), ...)
```

```
children(conceptIds, include_self = FALSE, SNOMED = getSNOMED(), ...)
```

```
descendants(conceptIds, include_self = FALSE, SNOMED = getSNOMED(), ...)
```

Arguments

conceptIds	character or integer64 vector of SNOMED concept IDs
include_self	whether to include the original concept(s) in the output, default = FALSE
SNOMED	environment containing a SNOMED dictionary
...	other arguments to pass to relatedConcepts

Value

a bit64 vector of SNOMED CT concepts

Examples

```
SNOMED <- sampleSNOMED()

parents('Heart failure')
children('Heart failure')
ancestors('Heart failure')
descendants('Heart failure')
```

print.SNOMEDcodelist *Display a SNOMEDcodelist on screen*

Description

Displays a SNOMEDcodelist on screen, including metadata. Truncates term descriptions in order to fit within the line width.

Usage

```
## S3 method for class 'SNOMEDcodelist'
print(x, ...)
```

Arguments

x	SNOMEDcodelist object to print to screen
...	not used

Value

invisibly returns the codelist

See Also

Other SNOMEDcodelist functions: [SNOMEDcodelist\(\)](#), [addInactiveConcepts\(\)](#), [expandSNOMED\(\)](#), [export\(\)](#), [is.SNOMEDcodelist\(\)](#)

print.SNOMEDconcept *Display a SNOMEDconcept object with descriptions*

Description

SNOMEDconcept is an S3 class for vectors of SNOMED concept IDs as 64-bit integers. This function checks whether the object has the class SNOMEDconcept and is a vector of 64-bit integers.

Usage

```
## S3 method for class 'SNOMEDconcept'  
print(x, ...)
```

Arguments

x	SNOMEDconcept object, or something that can be coerced to one
...	not required

Value

invisibly returns a character vector of the SNOMED CT concepts with descriptions separated by pipe (|)

See Also

Other SNOMEDconcept functions: [as.data.frame.SNOMEDconcept\(\)](#), [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [union.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

QUERY *Sample query table from SNOMED CT dictionary*

Description

Sample of the SNOMED CT table of ancestor / descendant relationships for inactive concepts.

Usage

```
data(QUERY)
```

Format

An object of class "data.table"

Details

- supertypeId integer64: concept ID of the ancestor (active) concept
- subtypeId integer64: concept ID of the descendant (inactive) concept
- provenance integer: provenance of relationship. Provenance = 0 means subsumption is always true. Provenance = 1 means subsumption is usually true (but there is a theoretical risk of false positives). Provenance = 2 means both ancestors and descendents are only approximately known. Provenance = 3 means original code had at least two distinct meanings and all are being returned

See Also

Other SNOMEDsample: [HISTORY](#), [SNOMED_RELATIONSHIP](#)

Examples

```
# Create a TEST environment and load the sample dictionaries
TEST <- new.env()
data(CONCEPT, envir = TEST)
data(DESCRIPTION, envir = TEST)
data(RELATIONSHIP, envir = TEST)
data(STATEDRELATIONSHIP, envir = TEST)
data(QUERY, envir = TEST)

# Show properties of the query table
str(TEST$QUERY)
```

Rdiagnosislist	<i>Rdiagnosislist: A package for manipulating SNOMED CT diagnosis lists</i>
----------------	---

Description

The Rdiagnosislist package makes it easy to load a SNOMED dictionary into R and use the hierarchies to search for concepts and navigate relations between concepts.

READMAPS	<i>Sample mappings from Read to SNOMED CT</i>
----------	---

Description

A sample of a mapping table derived from NHS Digital maps. Contains concepts in Read Clinical Terms Version 2 and Clinical Terms Version 3 that map to a set of SNOMED CT concepts, according to a supplied mapping file. The source data are available from the NHS Digital Technology Reference data Update Distribution <https://isd.digital.nhs.uk/trud/user/guest/group/0/pack/9/subpack/9/releases>.

Usage

```
data(READMAPS)
```

Format

An object of class "data.table"

Details

- conceptId integer64: SNOMED CT conceptId (primary key)
- read2_code list: character list of 7-character Read V2 codes
- read2_term list: character list of Read V2 terms
- ctv3_concept list: character list of CTV3 concept codes
- ctv3_termid list: character list of CTV3 term description codes

See Also

loadREADMAPS, getMaps

Examples

```
# Show properties of the READMAPS table
data(READMAPS)
str(READMAPS)
```

relatedConcepts

Obtain related concepts for a set of SNOMED CT concepts

Description

Returns concepts with a particular relation to a supplied set of SNOMED CT concepts

Usage

```
relatedConcepts(
  conceptIds,
  typeId = bit64::as.integer64("116680003"),
  tables = c("RELATIONSHIP", "STATEDRELATIONSHIP"),
  reverse = FALSE,
  recursive = FALSE,
  active_only = TRUE,
  SNOMED = getSNOMED()
)
```

Arguments

conceptIds	character or integer64 vector
typeId	concept ID of relationship type. Defaults to 116680003 = Is a
tables	vector of names of relationship table(s) to use; by default use both RELATIONSHIP and STATEDRELATIONSHIP
reverse	whether to reverse the relationship
recursive	whether to re-apply the function on the outputs
active_only	whether to limit the output to active concepts only
SNOMED	environment containing a SNOMED dictionary

Value

a data.table with the following columns: id, conceptId, type (only if include_synonyms = TRUE), term, active (only if active_only = FALSE)

Examples

```
# Load sample SNOMED CT dictionary
SNOMED <- sampleSNOMED()

# Example: anatomical site of a finding
findingSite <- function(x){
  relatedConcepts(as.SNOMEDconcept(x),
    typeId = as.SNOMEDconcept('Finding site'))
}

description(findingSite('Heart failure'))
# Heart structure (body structure)
```

sampleSNOMED	<i>Sample SNOMED CT dictionary</i>
--------------	------------------------------------

Description

Returns an environment containing a selection of SNOMED CT terms, their relationships and descriptions which are provided with the package

Usage

```
sampleSNOMED()
```

Value

environment containing four data.table objects: CONCEPT, DESCRIPTION, RELATIONSHIP, STATEDRELATIONSHIP and a list named 'metadata'

See Also

CONCEPT, DESCRIPTION, RELATIONSHIP, STATEDRELATIONSHIP, REFSET, SIMPLEMAP, EXTENDEDMAP, HISTORY, QUERY, loadSNOMED, sampleSNOMED

Examples

```
TEST <- sampleSNOMED()
inactiveIncluded(TEST)
SNOMEDconcept('Heart failure', SNOMED = TEST)

# To display metadata for this SNOMED CT dictionary
sampleSNOMED()$metadata
```

semanticType

Retrieves semantic types using the text 'tag' in the description

Description

Retrieves semantic types using the text 'tag' in the description

Usage

```
semanticType(conceptIds, SNOMED = getSNOMED())
```

Arguments

conceptIds character or integer64 vector of SNOMED concept IDs
 SNOMED environment containing a SNOMED dictionary

Value

a character vector of semantic tags corresponding to the conceptIDs

Examples

```
SNOMED <- sampleSNOMED()

semanticType(as.SNOMEDconcept(c('Heart failure', 'Is a')))
```

simplify	<i>Retrieves closest single ancestor within a given set of SNOMED CT concepts</i>
----------	---

Description

Returns a vector of SNOMED CT concept IDs for an ancestor of each concept that is within a second list. If multiple ancestors are included in the second list, the concept is not simplified (i.e. the original concept ID is returned). This functionality can be used to translate concepts into simpler forms for display, e.g. 'Heart failure' instead of 'Heart failure with reduced ejection fraction'.

Usage

```
simplify(
  conceptIds,
  ancestorIds,
  SNOMED = getSNOMED(),
  tables = c("RELATIONSHIP", "STATEDRELATIONSHIP")
)
```

Arguments

conceptIds	character or integer64 vector of SNOMED concept IDs for concepts for which an ancestor is sought
ancestorIds	character or integer64 vector of SNOMED concept IDs for possible ancestors
SNOMED	environment containing a SNOMED dictionary
tables	character vector of relationship tables to use

Details

This function is intended for use with active SNOMED CT concepts only.

Value

a data.table with the following columns: originalId (integer64) = original conceptId, ancestorId (integer64) = closest single ancestor, or original concept ID if no ancestor is included among ancestorIds

Examples

```
SNOMED <- sampleSNOMED()

original_terms <- c('Systolic heart failure', 'Is a',
  'Heart failure with reduced ejection fraction',
  'Acute kidney injury due to circulatory failure (disorder)')
# Note in this example 'Is a' has no parents in ancestors,
# and acute kidney failure has two parents in ancestors
```

```
# so neither of the parents will be chosen.
# Also test out inclusion of duplicate concepts.

ancestors <- simplify(c(as.SNOMEDconcept(original_terms),
  as.SNOMEDconcept(original_terms)[3:4]),
  as.SNOMEDconcept(c('Heart failure', 'Acute heart failure',
    'Cardiorenal syndrome (disorder)')))
print(cbind(original_terms, description(ancestors$ancestorId)$term))
```

 SNOMEDcodelist

 Convert a data.frame to a SNOMEDcodelist object

Description

SNOMEDcodelist is an S3 class for lists of SNOMED CT concepts. It consists of conceptId and include_desc columns. The option to include descendants allows the creation of more succinct SNOMED codelists.

Usage

```
SNOMEDcodelist(
  x,
  include_desc = FALSE,
  format = c("simple", "tree", "exptree"),
  codelist_name = NULL,
  version = NULL,
  author = NULL,
  date = NULL,
  SNOMED = getSNOMED(),
  show_excluded_descendants = FALSE
)

as.SNOMEDcodelist(x, ...)
```

Arguments

x	vector of SNOMED CT concept IDs, something which can be coerced to a SNOMEDconcept object, or a data.frame with a column 'conceptId' containing SNOMED CT concept IDs in integer64 or text format and optional column 'include_desc' (Boolean) stating whether descendants of the term should be included.
include_desc	Boolean vector stating whether descendants are included, recycled if necessary. Default = FALSE. Ignored if x contains a column 'include_desc'
format	Whether the codelist is expressed as a simple enumeration of concepts ('simple'), as a set of concept hierarchies ('tree'), or concept hierarchies showing all descendant terms ('exptree'). Codelists can be converted between the formats, but the result of conversion may depend on the SNOMED CT dictionary being used.

<code>codelist_name</code>	Name of the codelist (character vector of length 1)
<code>version</code>	Version of the codelist (character vector of length 1)
<code>author</code>	Author of the codelist (character vector of length 1)
<code>date</code>	Date attributed to the codelist (character vector of length 1)
<code>SNOMED</code>	environment containing a SNOMED dictionary
<code>show_excluded_descendants</code>	Whether to show excluded descendants alongside the codes included in the codelist (for a 'tree' or 'exptree' format codelist).
<code>...</code>	other arguments to pass to SNOMEDcodelist

Details

Input is a `data.frame` or `data.table` with column names 'conceptId' and optionally 'include_desc', which is `FALSE` by default, but if `TRUE` then the codelist automatically includes all active descendants of that concept.

If the codelist is intended to contain inactive concepts, it can only exist in the 'simple' format. Inactive concepts will be lost if the codelist is converted between formats.

`as.SNOMEDcodelist` converts its argument into a `SNOMEDcodelist` but leaves it unchanged if it is already a `SNOMEDcodelist`.

Value

An object of class 'SNOMEDcodelist'

See Also

`htmlCodelistHierarchy`

Other `SNOMEDcodelist` functions: `addInactiveConcepts()`, `expandSNOMED()`, `export()`, `is.SNOMEDcodelist()`, `print.SNOMEDcodelist()`

Other `SNOMEDcodelist` functions: `addInactiveConcepts()`, `expandSNOMED()`, `export()`, `is.SNOMEDcodelist()`, `print.SNOMEDcodelist()`

Examples

```
SNOMED <- sampleSNOMED()

my_concepts <- SNOMEDconcept('Heart failure')
SNOMEDcodelist(my_concepts)
SNOMEDcodelist(data.frame(conceptId = my_concepts))
as.SNOMEDcodelist(data.frame(conceptId = my_concepts,
  include_desc = TRUE))
```

SNOMED_CONCEPT *Sample concept table from SNOMED CT dictionary*

Description

A sample of the SNOMED CT concept table.

Usage

```
data(CONCEPT)
```

Format

An object of class "data.table"

Details

- id integer64: SNOMED CT conceptId (primary key)
- moduleId integer64: class of SNOMED CT concept (whether it is used for recording information or is a metadata concept)
- definitionStatusId integer64: 900000000000074008 = primitive concept, 900000000000073002 = defined by conditions
- effectiveTime IDate: when the concept became active
- active logical: whether this concept is currently active

Examples

```
# Show properties of the CONCEPT table
data('CONCEPT')
str(CONCEPT)
```

SNOMED_DESCRIPTION *Sample description table from SNOMED CT dictionary*

Description

A sample of the SNOMED CT description table. Each concept may have a fully specified name and may have any number of synonyms.

Usage

```
data(DESCRIPTION)
```

Format

An object of class "data.table"

Details

- id integer64: description ID
- moduleId integer64: class of SNOMED CT concept (whether it is used for recording information or is a metadata concept)
- conceptId integer64: SNOMED CT concept ID
- languageCode character: 'en' = English
- typeId integer64: 900000000000013009 = Synonym, 90000000000003001 = Fully Specified Name
- term character: term description
- caseSignificanceId integer64: 900000000000020002 = Initial character case sensitive, 900000000000017005 = Whole term case sensitive, 9000000000000448009 = Whole term case insensitive
- effectiveTime IDate: when the concept became active
- active logical: whether this concept is currently active

Examples

```
# Show properties of the DESCRIPTION table
data('DESCRIPTION')
str(DESCRIPTION)
```

SNOMED_EXTENDEDMAP *Sample extended map table from SNOMED CT dictionary*

Description

A sample of the SNOMED CT extended map table, containing maps to ICD-10 and OPCS4.

Usage

```
data(EXTENDEDMAP)
```

Format

An object of class "data.table"

Details

- moduleId integer64: core metadata concept: 449080006 = SNOMED CT to ICD-10 rule-based mapping module, 999000031000000106 = SNOMED CT United Kingdom Edition reference set module
- refsetId integer64: foundation metadata concept: 447562003 = ICD-10 complex map reference set, 1126441000000105 = Office of Population Censuses and Surveys Classification of Interventions and Procedures Version 4.9 complex map reference set, 999002271000000101 = International Classification of Diseases, Tenth Revision, Fifth Edition, five character code United Kingdom complex map reference set

- referencedComponentId integer64: SNOMED CT conceptId of the concept mapped
- mapGroup integer: mapping group
- mapPriority integer: priority of alternative maps (1 = highest)
- mapRule character: advice on mapping rule
- mapAdvice character: mapping advice
- mapTarget character: target ICD-10 or OPCS4 code. The optional period between the third and fourth character has been removed for consistency.
- mapCategoryId integer64: foundation metadata concept describing the quality of the map
- effectiveTime IDate: when the concept became active
- active logical: whether this concept is currently active

Examples

```
# Load the dataset and show its properties
data('EXTENDEDMAP')
str(EXTENDEDMAP)

# This EXTENDEDMAP table is part of the sample SNOMED CT dictionary
# Hence this should show the same properties as above
str(sampleSNOMED())$EXTENDEDMAP
```

SNOMED_REFSET

Sample refset table from SNOMED CT dictionary

Description

A sample of the SNOMED CT refset table. This contains SNOMED CT codelists that are used for particular operational or clinical purposes, and are curated by SNOMED CT. The id column of the refset table is not included, in order to save space.

Usage

```
data(REFSET)
```

Format

An object of class "data.table"

Details

- moduleId integer64: SNOMED CT core metadata concept, stating whether the refset is from the SNOMED CT core module or the UK extension.
- refsetId integer64: SNOMED CT conceptId of the refset. These concepts have semantic type 'foundation metadata concept'
- referencedComponentId integer64: SNOMED CT conceptId of the member of the refset
- effectiveTime IDate: when the concept became active
- active logical: whether this concept is currently active

Examples

```
# Load the dataset and show its properties
data('REFSET')
str(REFSET)

# This REFSET table is part of the sample SNOMED CT dictionary
# Hence this should show the same properties as above
str(sampleSNOMED())$REFSET)
```

SNOMED_RELATIONSHIP *Sample relationship tables from SNOMED CT dictionary*

Description

Samples of the SNOMED CT tables of stated relationships (RELATIONSHIP) and inferred relationships (RELATIONSHIP).

Usage

```
data(RELATIONSHIP); data(STATEDRELATIONSHIP)

STATEDRELATIONSHIP
```

Format

An object of class "data.table"

An object of class data.table (inherits from data.frame) with 329 rows and 10 columns.

Details

- id integer64: ID of the relationship record (primary key)
- active logical: whether this concept is currently active
- moduleId integer64: class of SNOMED CT concept (whether it is used for recording information or is a metadata concept)
- sourceId integer64: source SNOMED CT concept for the relationship
- destinationId integer64: destination SNOMED CT concept for the relationship
- relationshipGroup integer: group ID for relationships that are grouped
- characteristicTypeId integer64: 900000000000011006 = Inferred relationship
- modifierId integer64: 900000000000451002 = Existential restriction modifier
- effectiveTime IDate: when the concept became active
- typeId integer64: type of relationship, e.g. 116680003 = Is a, 42752001 = Due to, 246090004 = Associated finding, 363698007 = Finding site, 363702006 = Has focus

See Also

Other SNOMEDsample: [HISTORY](#), [QUERY](#)

Examples

```
# Create a TEST environment and load the sample dictionaries
TEST <- new.env()
data(CONCEPT, envir = TEST)
data(DESCRIPTION, envir = TEST)
data(RELATIONSHIP, envir = TEST)
data(STATEDRELATIONSHIP, envir = TEST)

# Show properties of the relationship tables
str(TEST$RELATIONSHIP)
str(TEST$STATEDRELATIONSHIP)
```

SNOMED_SIMPLEMAP	<i>Sample SIMPLE map table from SNOMED CT dictionary</i>
------------------	--

Description

A sample of the SNOMED CT SIMPLE map table, containing maps to ICD-10 and OPCS4.

Usage

```
data(SIMPLEMAP)
```

Format

An object of class "data.table"

Details

- `moduleId` integer64: core metadata concept: 900000000000207008 = SNOMED CT core module, 999000021000000109 = SNOMED CT United Kingdom clinical extension reference set module, 999000031000000106 = SNOMED CT United Kingdom Edition reference set module
- `refsetId` integer64: foundation metadata concept: 900000000000497000 = CTV3 simple map reference set, 446608001 = ICD-O simple map reference set, 1323081000000108 = Coronavirus disease 19 caused by severe acute respiratory syndrome coronavirus 2 test result communication to general practice concept simple map reference set, 1323091000000105 = Coronavirus disease 19 caused by severe acute respiratory syndrome coronavirus 2 test result communication to general practice description simple map reference set, 82551000000107 = National Health Service England National Genomic Test Directory whole genome sequencing test simple map reference set
- `referencedComponentId` integer64: SNOMED CT conceptId of the concept mapped
- `mapTarget` character: target ICD-O or CTV3 code
- `effectiveTime` IDate: when the concept became active
- `active` logical: whether this concept is currently active

Examples

```
# Load the dataset and show its properties
data('SIMPLEMAP')
str(SIMPLEMAP)

# This SIMPLEMAP table is part of the sample SNOMED CT dictionary
# Hence this should show the same properties as above
str(sampleSNOMED())$SIMPLEMAP
```

union.SNOMEDconcept *Set operations for SNOMEDconcept vectors*

Description

The default set functions in the base package do not handle integer64 vectors correctly, so this package also provides new generic functions for union, intersect and setdiff, which enable the appropriate object-specific function to be called according to the class of the vector. This means that SNOMEDconcept vectors will remain as SNOMEDconcept vectors when these functions are used.

Usage

```
## S3 method for class 'SNOMEDconcept'
union(x, y)

union(x, y)

## Default S3 method:
union(x, y)

## S3 method for class 'SNOMEDconcept'
intersect(x, y)

intersect(x, y)

## Default S3 method:
intersect(x, y)

## S3 method for class 'SNOMEDconcept'
setdiff(x, y)

setdiff(x, y)

## Default S3 method:
setdiff(x, y)
```

Arguments

x	SNOMEDconcept vector
y	SNOMEDconcept vector, or an object that can be coerced to SNOMEDconcept by as.SNOMEDconcept

Value

an integer64 vector of SNOMEDconcept class

See Also

Other SNOMEDconcept functions: [as.data.frame.SNOMEDconcept\(\)](#), [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

Other SNOMEDconcept functions: [as.data.frame.SNOMEDconcept\(\)](#), [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

Other SNOMEDconcept functions: [as.data.frame.SNOMEDconcept\(\)](#), [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

Other SNOMEDconcept functions: [as.data.frame.SNOMEDconcept\(\)](#), [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

Other SNOMEDconcept functions: [as.data.frame.SNOMEDconcept\(\)](#), [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

Other SNOMEDconcept functions: [as.data.frame.SNOMEDconcept\(\)](#), [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

Other SNOMEDconcept functions: [as.data.frame.SNOMEDconcept\(\)](#), [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

Other SNOMEDconcept functions: [as.data.frame.SNOMEDconcept\(\)](#), [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [unique.SNOMEDconcept\(\)](#)

Examples

```
sys_acute <- SNOMEDconcept(c('Systolic heart failure',
  'Acute heart failure'), SNOMED = sampleSNOMED())
acute_left_right <- SNOMEDconcept(c('Acute heart failure',
  'Left heart failure', 'Right heart failure'),
  SNOMED = sampleSNOMED())
union(sys_acute, acute_left_right)
intersect(sys_acute, acute_left_right)
setdiff(sys_acute, acute_left_right)
```

unique.SNOMEDconcept *Unique vector of SNOMED CT concepts*

Description

SNOMEDconcept is an S3 class for vectors of SNOMED concept IDs as 64-bit integers. This function returns a vector containing only unique SNOMEDconcept values.

Usage

```
## S3 method for class 'SNOMEDconcept'  
unique(x, ...)
```

Arguments

x	SNOMEDconcept vector
...	other variables to pass on to the underlying 'unique' function

Value

SNOMEDconcept vector with duplicates removed

See Also

Other SNOMEDconcept functions: [as.data.frame.SNOMEDconcept\(\)](#), [c.SNOMEDconcept\(\)](#), [is.SNOMEDconcept\(\)](#), [print.SNOMEDconcept\(\)](#), [union.SNOMEDconcept\(\)](#)

Examples

```
hf <- SNOMEDconcept('Heart failure', SNOMED = sampleSNOMED())  
hf2 <- c(hf, hf)  
unique(hf2)
```

Index

- * **SNOMEDcodelist functions**
 - addInactiveConcepts, 2
 - expandSNOMED, 7
 - export, 9
 - is.SNOMEDcodelist, 17
 - print.SNOMEDcodelist, 22
 - SNOMEDcodelist, 29
- * **SNOMEDconcept functions**
 - as.data.frame.SNOMEDconcept, 3
 - c.SNOMEDconcept, 5
 - is.SNOMEDconcept, 18
 - print.SNOMEDconcept, 23
 - union.SNOMEDconcept, 36
 - unique.SNOMEDconcept, 38
- * **SNOMEDsample**
 - HISTORY, 14
 - QUERY, 23
 - SNOMED_RELATIONSHIP, 34
- * **datasets**
 - HISTORY, 14
 - QUERY, 23
 - READMAPS, 24
 - SNOMED_CONCEPT, 31
 - SNOMED_DESCRIPTION, 31
 - SNOMED_EXTENDEDMAP, 32
 - SNOMED_REFSET, 33
 - SNOMED_RELATIONSHIP, 34
 - SNOMED_SIMPLEMAP, 35
- addInactiveConcepts, 2, 8, 9, 18, 22, 30
- ancestors (parents), 21
- as.data.frame.SNOMEDconcept, 3, 6, 18, 23, 37, 38
- as.integer64.SNOMEDconcept
 - (as.data.frame.SNOMEDconcept), 3
- as.SNOMEDcodelist (SNOMEDcodelist), 29
- as.SNOMEDconcept
 - (as.data.frame.SNOMEDconcept), 3
- attrConcept, 4
- c.SNOMEDconcept, 4, 5, 18, 23, 37, 38
- children (parents), 21
- CONCEPT (SNOMED_CONCEPT), 31
- contractSNOMED (expandSNOMED), 7
- createSNOMEDindices, 6
- descendants (parents), 21
- DESCRIPTION (SNOMED_DESCRIPTION), 31
- description, 6
- expandSNOMED, 3, 7, 9, 18, 22, 30
- export, 3, 8, 9, 18, 22, 30
- exportSNOMEDenvir, 9
- EXTENDEDMAP (SNOMED_EXTENDEDMAP), 32
- getMaps, 10
- getRefset, 12
- getSNOMED, 12
- hasAttributes, 13
- HISTORY, 14, 24, 35
- htmlCodelistHierarchy, 15
- inactiveIncluded, 16
- intersect (union.SNOMEDconcept), 36
- is.SNOMEDcodelist, 3, 8, 9, 17, 22, 30
- is.SNOMEDconcept, 4, 6, 18, 23, 37, 38
- loadREADMAPS, 19
- loadSNOMED, 20
- parents, 21
- print.SNOMEDcodelist, 3, 8, 9, 18, 22, 30
- print.SNOMEDconcept, 4, 6, 18, 23, 37, 38
- QUERY, 15, 23, 35
- Rdiagnosislist, 24
- READMAPS, 24

REFSET (SNOMED_REFSET), 33
relatedConcepts, 25
RELATIONSHIP (SNOMED_RELATIONSHIP), 34

sampleSNOMED, 26
semanticType, 27
setdiff (union.SNOMEDconcept), 36
showCodeListHierarchy (expandSNOMED), 7
SIMPLEMAP (SNOMED_SIMPLEMAP), 35
simplify, 28
SNOMED_CONCEPT, 31
SNOMED_DESCRIPTION, 31
SNOMED_EXTENDEDMAP, 32
SNOMED_REFSET, 33
SNOMED_RELATIONSHIP, 15, 24, 34
SNOMED_SIMPLEMAP, 35
SNOMED_STATEDRELATIONSHIP
 (SNOMED_RELATIONSHIP), 34
SNOMEDcodelist, 3, 8, 9, 18, 22, 29
SNOMEDconcept
 (as.data.frame.SNOMEDconcept),
 3
STATEDRELATIONSHIP
 (SNOMED_RELATIONSHIP), 34

union (union.SNOMEDconcept), 36
union.SNOMEDconcept, 4, 6, 18, 23, 36, 38
unique.SNOMEDconcept, 4, 6, 18, 23, 37, 38